

INTERNATIONAL_GASES_AND_CHEMICALS_LTD

MATERIAL SAFETY DATA SHEETS

DATE: 4/05/01

SUPPLIER ADDRESS: SPEEDWELL RD
PARKHOUSE EAST
NEWCASTLE-U-LYME

EMERGENCY PHONE: (178) 256-5556
NUMBER

1. CHEMICAL PRODUCT

PRODUCT NAME: CIS-2-BUTENE

SYNONYMS: Dimethylethylene

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
CIS-2-BUTENE	C4H8	590-18-1	99+%	NE	NE	NE	NE

Note: NE = NONE ESTABLISHED

3. HAZARD IDENTIFICATION

*** EMERGENCY OVERVIEW ***

Flammable liquid and gas under pressure.
Can form explosive mixtures with air.
May cause frostbite.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Inhalation may cause asphyxiation due to dilution of available oxygen in the air. Symptoms include lightheadedness, giddiness, disorientation, shortness of breath, and possible cardiac arrhythmias. Skin and eye irritation may occur. Pressure drop through valves and piping may cause extreme cold and frostbite on contact.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US Only):

NTP - No

IARC MONOGRAPHS - No

OSHA REGULATED - No

Continued ...

4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: Immediately flush with copious amounts of water for at least 15 minutes.

SKIN CONTACT: If frostbite occurs, flush affected areas with lukewarm water.

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

5. FIRE FIGHTING MEASURES

FLASH POINT: 37.8 deg.C

AUTOIGNITION TEMPERATURE: 325 deg.C

FLAMMABLE LIMITS: Vol.%

LOWER: 1.7

UPPER: 9.0

EXTINGUISHING MEDIA: Carbon dioxide, foam, or dry chemical.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

HAZARDOUS COMBUSTION PRODUCTS: Toxic carbon monoxide may be given off during combustion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions. Vapors may travel a considerable distance to the source of ignition and flash back. May form explosive mixture in air.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat. Remove sources of ignition and combustibles.

SPECIALIZED EQUIPMENT: None

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Store away from oxidizers, combustible materials, and source of ignition or heat. Keep valve protection cap on cylinders when not in use.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentrations below flammable limits.

PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses

SKIN PROTECTION: Protective gloves to prevent contact with cold equipment.

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless

ODOR: Slightly aromatic

PHYSICAL STATE: Gas

VAPOR PRESSURE: @21 deg.C: 27.3 psia

VAPOR DENSITY (AIR=1): 1.9

BOILING POINT (C): 3.7

SOLUBILITY IN WATER: Insoluble

Continued ...

SPECIFIC GRAVITY (H2O=1): @25 deg.C: 0.6
EVAPORATION RATE: (Ethyl Ether=1) >1.0
ODOR THRESHOLD: N/Av

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Toxic carbon monoxide.

11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC50): None established

LETHAL DOSE 50 (LD50): N/Av

TERATOGENICITY: N/Av

REPRODUCTIVE EFFECTS: N/Av

MUTAGENICITY: N/Av

12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14. TRANSPORT INFORMATION

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Liquefied gas, flammable, n.o.s.

HAZARD CLASS: 2.1 (flammable)

IDENTIFICATION NUMBER: UN3161

REPORTABLE QUANTITIES: None

LABELING: FLAMMABLE GAS

ADR/RID (EU Only): Class 2, 2F

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

15. REGULATORY INFORMATION

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: N/Av

NUMBER IN ANNEX 1 OF DIR 67/548: Material is listed in annex 1.

EU CLASSIFICATION: N/Av

R: N/Av

S: N/Av

16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS:

N/Av - Not Applicable

N/Av - Not Available

SA - Simple Asphyxiant

NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.