

INTERNATIONAL\_GASES\_AND\_CHEMICALS\_LTD

## MATERIAL SAFETY DATA SHEETS

DATE: 11/18/03

SUPPLIER ADDRESS: SPEEDWELL RD  
PARKHOUSE EAST  
NEWCASTLE-U-LYME

EMERGENCY PHONE: (178) 256-5556  
NUMBER

---

1. CHEMICAL PRODUCT

---

PRODUCT NAME: DEUTERIUM

SYNONYMS: Heavy Hydrogen

---

2. COMPOSITION, INFORMATION ON INGREDIENTS

---

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
DEUTERIUM	D2	7782-39-0	99+%	S/A	NE	NE	S/A

Note: S/A = SIMPLE ASPHYXIANT  
NE = NONE ESTABLISHED

---

3. HAZARD IDENTIFICATION

---

## \*\*\* EMERGENCY OVERVIEW \*\*\*

Flammable high pressure gas.  
Can form explosive mixtures with air.  
May ignite if valve is open to air.  
Burns with an invisible flame.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Material acts as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENICITY (US Only):

NTP - No  
IARC MONOGRAPHS - No  
OSHA REGULATED - No

Continued ...

---

#### \_4.\_FIRST\_AID\_MEASURES

---

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: None

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

---

#### \_5.\_FIRE\_FIGHTING\_MEASURES

---

FLASH POINT: Gas

AUTOIGNITION TEMPERATURE: 570 deg.C

FLAMMABLE LIMITS: Vol.%

LOWER: 5

UPPER: 75

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, or halogenated gas.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Do not extinguish a gas fire unless immediate shut-off of gas flow is possible. Explosive vapor could form. Keep fire exposed cylinders cool with water spray.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions. Severe when exposed to heat or flame. Contact with strong oxidizers may cause a fire or explosion. Burns with an invisible flame. Vapors may travel a considerable distance to the source of ignition and flash back.

---

#### \_6.\_ACCIDENTAL\_RELEASE\_MEASURES

---

CLEAN UP PROCEDURES: Evacuate and ventilate area. Shut off source if possible and remove source of heat. Remove all sources of ignition. Remove

leaking cylinder to exhaust hood or safe outdoor area. Allow gas to discharge at a slow rate into an exhaust hood or safe outdoor area.

SPECIALIZED EQUIPMENT: Use non-sparking tools.

---

#### \_7.\_HANDLING\_AND\_STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders. No part of cylinder should be exposed to temperatures above 52 degrees celsius. Use explosion proof ventilation, piping, and equipment.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use. Quantities greater than 400 standard cubic feet should be stored in specially ventilated rooms or outside. Store away from oxidizers, combustible materials, and source of ignition or heat.

---

#### 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

---

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentrations below exposure and flammable limits.

##### PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses

SKIN PROTECTION: None

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

---

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE: Colorless

ODOR: Odorless

PHYSICAL STATE: Gas

VAPOR PRESSURE: Gas

VAPOR DENSITY (AIR=1): 0.14

BOILING POINT (C): -249.6

Continued ...

SOLUBILITY IN WATER: Insoluble  
SPECIFIC GRAVITY (H2O=1): @-235 deg.C:  
0.169  
EVAPORATION RATE: N/Av  
ODOR THRESHOLD: N/Ap

---

## 10. STABILITY AND REACTIVITY

---

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Oxidizing agents. Alkali and alkaline earth metals.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None

---

## 11. TOXICOLOGICAL INFORMATION

---

LETHAL CONCENTRATION (LC50): None established

LETHAL DOSE 50 (LD50): N/Av

TERATOGENICITY: N/Av

REPRODUCTIVE EFFECTS: N/Av

MUTAGENICITY: N/Av

---

## 12. ECOLOGICAL INFORMATION

---

No adverse ecological effects are expected.

---

## 13. DISPOSAL CONSIDERATIONS

---

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

---

## 14. TRANSPORT INFORMATION

---

CONCENTRATION: 99+%

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Deuterium, compressed

HAZARD CLASS: 2.1 (flammable)

IDENTIFICATION NUMBER: UN1957

REPORTABLE QUANTITIES: None  
LABELING: FLAMMABLE GAS

ADR/RID (EU Only): Class 2, 1F

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

---

## 15. REGULATORY INFORMATION

---

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: N/Av

NUMBER IN ANNEX 1 OF DIR 67/548: Not listed in annex 1.

EU CLASSIFICATION: N/Av

R: N/Av

S: N/Av

---

## 16. OTHER INFORMATION

---

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS:

N/Av - Not Applicable

N/Av - Not Available

SA - Simple Asphyxiant

NE - None Established

DISCLAIMER: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.